

cm.		B Höhe geöffnet (in cm)									
		С	240								
		D Bodenfreiheit* (in cm)									
	7	,	8	9	10	11	12	13			
	14	6	166	186	206	226	246	266			
	12	2	138	155	171	188	205	221			
	8.	1	92	103	114	125	136	148			
	15	7	164	172	183	196	212	235			
	14	-0	160	180	200	220					
	140		160	180	200	220					
	0		0	0	0	0					
	197		204	212	222	236					
	14	12									
	C)									
1	1 4	_									

13.5

55

80

423

Fläche (in m²)

Schirmgewicht (in kg)

Transportgewicht (in kg)

A Höhe geschlossen (in cm)

	Zwischenspeiche Kurz	Diagonalspeiche		
1	Y - Richtung			
300 cm	(S) (S) (S)	Zwischen- speiche		
300	X - Richtung	Lang		
<u> </u>	450 cm			

Messpunkte von Schirmmitte		2	3	4	5	6	7	8	9	10	11	12
Abstand in Richtung Diagonalspeiche (in cm)		42	66	86	106	126	146	166	186	206	226	24
Abstand in X - Richtung (in cm)		38	55	72	88	105	122	138	155	171	188	20
Abstand in Y - Richtung (in cm)		26	37	48	59	70	81	92	103	114	125	13
Bodenfreiheit* (in cm)		138	140	143	147	151	157	164	172	183	196	21
Abstand in Richtung Zwischenspeiche Lang (in cm)	20	40	60	80	100	120	140	160	180	200	220	
Abstand in X - Richtung (in cm)		40	60	80	100	120	140	160	180	200	220	
Abstand in Y - Richtung (in cm)		0	0	0	0	0	0	0	0	0	0	
Bodenfreiheit* (in cm)		181	182	185	188	192	197	204	212	222	236	
Abstand in Richtung Zwischenspeiche Kurz (in cm)		42	62	82	102	122	142					
Abstand in X - Richtung (in cm)		0	0	0	0	0	0					
Abstand in Y - Richtung (in cm)		42	62	82	102	122	142					
Bodenfreiheit* (in cm)		248	248	249	249	248	244					